



I/F No:

No	Symbol
1	V0
2	VDD
3	VSS
4	DB7
5	DB6
6	DB5
7	DB4
8	DB3
9	DB2
10	DB1
11	DB0
12	E
13	R/W
14	RS



- NOTES:
1. GENERAL TOLERANCE;
 2. () IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. RoHS COMPLIANT.

Display Type	TN
	POSITIVE
	REFLECTIVE
Front Polarizer	NORMAL
Driving Method	1/16 DUTY,1/5 BIAS
Viewing Direction	6 O'CLOCK
LCD Driver IC	CC5016/CGROM NO:51(0)
Logic Voltage (V)	5.0V
LCD Driving Voltage	4.6V
Operation Temperature	0°C TO 50°C
Storage Temperature	-20°C TO 70°C
Interface	PARALLEL
Backlight	NIL

					ME.CHECKED	HJW	2011-07-07	TITLE MODULE SPEC.	DRAWING NO. STR-TC3108				
					EE.CHECKED	ZY	2011-07-07		UNIT				
					PE.CHECKED	WYL	2011-07-07		mm		SCALE	FIT	
					APPROVED	DXH	2011-07-07		3rd Angle		SHEET 1 OF 1		
01		FIRST ISSUE		HJW	11-07-07	CUSTOMER'S APPROVAL		BOM NO. : BM110629-06	TRUEVISION TECHNOLOGIES LTD				
VER.	SYMBOL	DESCRIPTION OF CHANGES		SIGN	DATE								