



PIN ASSIGNMENT

NO	SYMBOL	NO	SYMBOL
1	NC	27	NC
2	IRS	28	VDD
3	HPM	29	DB7
4	VDD	30	DB6
5	VR	31	DB5
6	V5	32	DB4
7	V4	33	DB3
8	V3	34	DB2
9	V2	35	DB1
10	V1	36	DB0
11	VDD	37	NC
12	VSS	38	RD,E
13	CAP2+	39	WR,R/W
14	CAP2-	40	A0
15	CAP1-	41	RES
16	CAP1+	42	NC
17	CAP3-	43	CS1
18	VOUT	44	NC
19	VSS2	45	NC
20	NC	46	NC
21	NC	47	NC
22	NC	48	NC
23	NC	49	NC
24	VSS	50	NC
25	NC	51	NC
26	NC	52	NC

- NOTE:
- 1, GENERAL TOLERANCE:  $\pm 0.2$ .
  - 2, (...) IS REFERENCE DIMENSION.
  - 3, COMPLY ROHS.
  - 4, \* CRITICAL DIMENSION.

Display Type	STN
	NEGATIVE
	TRANSMISSIVE
Front Polarizer	
Operating Method	1/65 DUTY,1/9 BIAS
Viewing Angle	12 O'CLOCK
LCD Driver IC	S1D15605
Operating Voltage	VDD=5.0V VLCD=12.5V
Operation Temperature	-10°C TO 60°C
Storage Temperature	-20°C TO 70°C
Interface	
Backlight	

					DRAWN	CL	TITLE	DRAWING NO.			
					ME.CHECKED	XB	MODULE SPEC.	STR-TG0865			
					EE.CHECKED	YY		UNIT	mm	SCALE	FIT
					PE.CHECKED			3rd Angle		SHEET 1 OF 1	
					APPROVED	LDK		TRUEVISION TECHNOLOGIES LTD			
01		first issue	CL	09.08.03	CUSTOMER'S APPROVAL						
VER.	SYMBOL	AMENDMENT	SIGN	DATE							