


LED WHITE 2*2Dies



Pin No	Symbol
1	NC
2	IRS
3	PS
4	CB6
5	VR
6	V0
7	V4
8	V3
9	V2
10	V1
11	CN2
12	CP2
13	CP1
14	CN1
15	CP3
16	NC
17	VOUT
18	VSS
19	VSS
20	VDD
21	VDD
22	DB7
23	DB6
24	DB5
25	DB4
26	DB3
27	DB2
28	DB1
29	DB0
30	/RD
31	/WR
32	AD
33	/RES
34	/CS1

DISPLAY TYPE	ESTN POSITIVE TRANSMISSIVE
FRONT POLARIZER	
OPERATING METHOD	1/64DUTY,1/9BIAS
OPERATION VOLTAGE	VDP=9.0V VDD=3V
IC	NT7538
VIEWING ANGLE	6:00
OPERATION TEMPERATURE	-20°C TO 70°C
STORAGE TEMPERATURE	30°C TO 80°C
CONNECTOR TYPE	FPC+COG IC+LCD
BACKLIGHT COLOR	VF=3.0+/-0.3V IF=30mA

NOTE:
 1. GENERAL TOLERANCE: ±0.2.
 2. (..) IS REFERENCE DIMENSION.
 3. * CRITICAL DIMENSION
 4. COMPLYABLY RoHS.

					DRAWN	ZQ	TITLE	DRAWING NO.			
					EE.CHECKED	TJP	MODULE SPEC.	STR-TG3157			
					PE.CHECKED	TJP		UNIT mm SCALE FIT			
					APPROVED	HJB		3rd Angle SHEET 1 OF 1			
01		First issue	ZQ	14.04.11	CUSTOMER'S APPROVAL		BOM NO.:BM140227-03A	TRUEVISION TECHNOLOGIES LTD.			
VER.	SYMBOL	AMENDMENT	SIGN	DATE							