




PIN	SIGNAL
1	GND
2	VG
3	XV0
4	V0
5	VDD
6	VSS
7	CS
8	A0
9	RST
10	SDA
11	SCL
12	GND

- NOTE:
1. GENERAL TOLERANCE:  $\pm 0.2$ .
  2. (...) IS REFERENCE DIMENSION.
  3. \* CRITICAL DIMENSION
  4. RoHS COMPLIANT
  5. FPC golden finger Ni thickness: 3.0-5.0um, Au thickness:  $> 0.03\mu\text{m}$



DOTS DETAIL (10:1)



CIRCUIT DIAGRAM ( 10pcs white leds )

Display Type	STN(BLUE)
	NEGATIVE
	TRANSMISSIVE
Front Polarizer	NORMAL
Operating Method	1/65 DUTY, 1/9 BIAS
Viewing Angle	6 O'CLOCK
LCD Driver IC	ST7525
Operating Voltage	VDD=3.3V VLCD=9.2V
Operation Temperature	-20°C TO 50°C
Storage Temperature	-30°C TO 60°C
High Temperature/Humidity Storage	
Interface	SPI
Backlight	10LED WHITE(3.3V ,150mA)

VER.	SYMBOL	AMENDMENT	SIGN	DATE	CUSTOMER'S APPROVAL	DRAWN	WKL	TITLE	DRAWING NO.			
						EE.CHECKED	MWW	MODULE SPEC.	STR-TG9307			
						ME.CHECKED	MWW		UNIT mm SCALE FIT			
						APPROVED	HJB		SHEET 1 OF 1			
		first issue	WKL	14.06.30				BOM NO.: BM140623-07A	3rd Angle			
TRUEVISION TECHNOLOGIES LTD												