


INTERFACE	
1	VDD
2	VSS
3	V0
4	DB0
5	DB1
6	DB2
7	DB3
8	DB4
9	DB5
10	DB6
11	DB7
12	CS2
13	CS1
14	RST
15	RW
16	RS
17	E
18	VSS
19	LED-A(+5V)
20	LED-K

VER	DETIAL DISCRIPTION	DATE
00	FIRST ISSUE	2012-4-27



SPECIFICATION:

- 1). STN(GARY)/POSTIVE/TRANSFLECTIVE
- 2). DUTY:1/64. BIAS:1/9. VOP=9.0V
- 3). VIEWING ANGLE: 6 O'CLOCK
- 4). DRIVE VOLTAGE: 5.0V
- 5). OPERATING TEMPERATURE: -20~70°C
STORAGE TEMPERATURE: -30~80°C
- 6). BACKLIGHT: WHITE I=60MA
- 7). DRIVE IC: 0108, 0107

TrueVision Technologies Limited www.tvtdisplay.com

Unspecified Tolerance:	± 0.20	INITS: mm	DATE:	MODE NUMBER :		SHEET:	1 Of 1
DESIGN BY:	WZQ	2012/4/27		HSM12864G		DATE:	2012/4/27
CHECKED BY:							
CUSTOM NO:				DO NOT SCALE THIS DRAWING.	PROJECTION		