



1	LEDK
2	LEDA
3	GND
4	VCC
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	R1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	CLK
31	DISP
32	HSYNC
33	VSYNC
34	DEN
35	NC
36	GND
37	XR
38	YD
39	XL
40	YU

1. 带*尺寸为重点尺寸，带（）尺寸为参考尺寸
2. LCD切割断面崩边 $\leq 1/3$ （单层LCD厚度）
3. 平面翘曲度 $\leq 0.35\text{mm}$
4. 符合RoHS指令
5. 工作温度： $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$
6. 储存温度： $-30^{\circ}\text{C} \sim 80^{\circ}\text{C}$
7. 建议TP V. A开窗比LCD A. A单边大0.4mm
8. 泡棉开窗比LCD A. A单边大0.3mm

A		首次发行	xw	2022.3.5
REV	SI GN	DESCRIPTION	PI C	DATE

PART DESCRIPTION	LCM		TrueVision Technologies Limited www.tvtdisplay.com				
DESIGNED			UNIT mm	SCALE 1.00	3rd ANGLE 	SIZE A4	SHEET NUMBER 1 of 1
CHECKED			PART NUMBER				DRAWING REV. A
APPROVED			MODEL NAME TFT043BT005				PART NUMBER VER N/A