


QSPI	
MAIN	FPC PIN DESCRIPTION
1	TP_VCC
2	TP_INT
3	TP_SDA
4	TP_SCL
5	TP_RST
6	GND
7	SPI_CS
8	SPI_IO0
9	SPI_IO3
10	GND
11	SPI_CLK
12	GND
13	SPI_IO1
14	SPI_IO2
15	SPI_RST
16	TE
17	WIRE(NC)
18	GND
19	IO_VCC
20	VCC
21	NC
22	LEDA
23	LEDK
24	MTP_PWR

PIN	DESCRIPTION	17	WIRE(NC)
1	TP_VCC	18	GND
2	TP_INT	19	IO_VCC
3	TP_SDA	20	VCC
4	TP_SCL	21	NC
5	TP_RST	22	LEDA
6	GND	23	LEDK
		24	MTP_PWR

LCD型号/类型/分辨率	B0E1.46/IPS/360*360
视觉方向	ALL
贴片方式	上细砂0° /下增亮90°
驱动IC	ST77916
LED颗数/连接方式/电流	

1. 未标注尺寸公差±0.20mm
2. LCD切割断面崩边≤1/3（单层LCD厚度）
3. 平面翘曲度≤0.35mm
4. 符合RoHS指令
5. 工作温度：-20℃~70℃
6. 储存温度：-30℃~80℃
7. 建议TP、VA开窗比LCD A.A单边大0.4mm
8. 泡棉开窗比LCD A.A单边大0.3mm



A		首次发行	BILL	2023.04.1
REV	SIGN	DESCRIPTION	PIC	DATE

PART DESCRIPTION		LCM		TrueVision Technologies Limited				
DESIGNED			UNIT mm	SCALE 1.00	3rd ANGLE		SIZE A4	SHEET NUMBER 1 of 1
CHECKED			PART NUMBER					DRAWING REV. A
APPROVED			MODEL NAME TFT146B005					PART NUMBER N/A